

DeepSeek 大语言模型 API 接口

[English](#) | 中文

[@deepseek-ai/dsh-llm-deepseek](#) | [deepseek-official](#) | [DeepSeek Harness](#) | HTTP | JSON | [llm-pi-ai](#)

`baseUrl` | `messages` | `schema` | `token`

--	--	--	--	--	--	--	--	--	--

Header	Content	Value
HTTP Header	kebab-case HTTP Header	user-agent, x-deepseek-harness-session-id
DeepSeek Header	dsh_ snake case	dsh_plugin_packages, dsh_session_log
DSH Header JSON	Camel case	afterSeq, throughSeq, sessionId
Footer	kebab-case domain/action	session-log-deepseek/delivery-accepted

`version` | JSON |

[DeepSeekLlmApiExtensionRegistry](#) | DeepSeek | HTTP |

--	--	--	--

Header	Content	Value
user-agent	HTTP Files API	product/version (+url) deepseek- harness
x-deepseek-harness-user-id		Harness home UUID
x-deepseek-harness-session-id	id	sessionId
x-deepseek-harness-compact	compaction	1

`x-deepseek-harness-session-id` | `sessionId` | `id`



messages sessionId purpose undefined

JSON HTTP

HTTP 2x> accept() SSE 2xx HTTP SSE

dsh_plugin_packages

[@deepseek-ai/dsh-plugin-package-inventory-deepseek](#) Loader-backed

```
{
  "dsh_plugin_packages": {
    "version": 1,
    "packages": [
      {
        "name": "@deepseek-ai/dsh-example",
        "version": "0.1.1-rc.2"
      }
    ]
  }
}
```

version	1	dsh_plugin_packages schema
packages		
packages[].name		manifest npm
packages[].version		manifest

Loader standing agent-preset manifest

(name, version) name version

pendingfailedunloadingdisposed Loader fiber

packages: [] dsh_plugin_packages

dsh_session_log

[@deepseek-ai/dsh-session-log-deepseek](#)

id

```
{
  "dsh_session_log": {
    "version": 1,
    "session": {
      "version": 0,
      "id": "session-id",
      "createdAt": 17800000000000
    },
    "afterSeq": -1,
    "throughSeq": 0,
    "events": [
      {
        "type": "turn/start",
        "seq": 0,
        "time": 17800000000001,
        "data": {
          "turn": 1
        }
      }
    ]
  }
}
```

名前	型	初期値
version	int	dsh_session_log の schema 番号
session	int	SessionHeader
afterSeq	int	-1 (16bit)
throughSeq	int	(8bit)
events	int	afterSeq + 1 (throughSeq) (4bit)

afterSeq: -1 id watermark



session [Session.header [dsh_session_log.version []]] sch session.version []

version		[0 []]
id		[] id
createdAt		[] Unix epoch []
cwd		[]
parentSession		fork [] id
seedLength		[] seed []
origin		subagent [subagent]
delegationDepth		[] subagent []
agentPreset		[] agent preset id

[]

[events [SessionEvent [type seq time [data [ignorable: true [sourceEventSeqs [surfaceOp []]]]]]]

[]

[] HTTP 2xx []

```
{
  "type": "session-log-deepseek/delivery-accepted",
  "seq": 8,
  "time": 1780000000002,
  "data": {
    "sessionId": "session-id",
    "throughSeq": 7
  }
}
```

delivery-accepted [] LLM [throughSeq > sessionId []

[throughSeq [] fork [] id []

[] 2xx []



Harness dsh_plugin_packages dsh_session_log assistant
baseUrl
version ignorable: true

#1
 3 2026 17:10:46
 3 2026 17:36:27